

## Specification Sheet

Part Number: T250I9X2



Heavy Duty Cable Tie, 28.7" Long, UL Rated, 250lb Tensile Strength, PA66, Natural, 25/pkg

Article Number	111-25219
Type	T250I
Color	Natural (NA)
Features & Benefits	<ul style="list-style-type: none"><li>• Heavy-duty design offers higher tensile strength.</li><li>• Buckle feature on head allows excess strap to be tucked away after installation.</li><li>• Bent tail ensures a quick and simple installation.</li></ul>
Quantity Per	bag

### Product Description

These cable ties offer a high minimum tensile strength and have a buckle feature which allows the end of the cable tie to be tucked away if necessary. The buckle also snaps into HellermannTyton lashing tie mounts (LTM.) T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

<b>Short Description</b>	Heavy Duty Cable Tie, 28.7" Long, UL Rated, 250lb Tensile Strength, PA66, Natural, 25/pkg
<b>Global Part Name</b>	T250I-PA66-NA
<b>Minimum Tensile Strength (Imperial)</b>	250.0
<b>Minimum Tensile Strength (Metric)</b>	1115.0
<b>Length L (Imperial)</b>	28.7
<b>Length L (Metric)</b>	730.0
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.49
<b>Width W (Metric)</b>	12.4
<b>Bundle Diameter Min (Imperial)</b>	0.47
<b>Bundle Diameter Min (Metric)</b>	12.0
<b>Bundle Diameter Max (Imperial)</b>	8.0
<b>Bundle Diameter Max (Metric)</b>	203.0

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V2
<b>Halogen free</b>	Yes
<b>Operating Temperature (Metric)</b>	-40°F to +185°F (-40°C to +85°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	UL   ANSI/UL 62275 UL   ANSI/UL 1565 UL   ANSI/UL 746B
<b>UL Recognized (US)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>Package Quantity(Imperial)</b>	25
<b>Package Quantity (Metric)</b>	25
<b>Customs Number</b>	3926909987
<b>Content Unit(BMEcat)</b>	pcs.
<b>Weight (Metric)</b>	17.6

