

Wireless module - FL WLAN EPA - 2692791

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




WLAN Ethernet Port Adapter, as a wireless connection from an Ethernet interface to a WLAN Access Point.

Why buy this product

- Integrated special antenna (EPA)
- Maximum security according to IEEE 802.11i with AES encryption
- IP65 protection class

Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 422420
GTIN	4046356422420

Technical data

Dimensions

Width	66 mm
Height	91 mm
Depth	34 mm
Note on dimensions	Without M12 connections

Ambient conditions

Ambient temperature (operation)	-40 °C ... 65 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Permissible humidity (operation)	5 % ... 90 % (non-condensing)
Permissible humidity (storage/transport)	5 % ... 90 % (non-condensing)
Air pressure (operation)	795 hPa ... 1080 hPa (up to 2000 m above sea level)
Degree of protection	IP65

Ethernet interface

Wireless module - FL WLAN EPA - 2692791

Technical data

Ethernet interface

Interface	Ethernet
Number	1
Connection method	M 12 connectors (D-coded, female)

Wireless interface

Designation	Wireless LAN
Wireless standard	IEEE 802.11
	b
	g
	n
Antenna connection method	(Internal)
Frequency range	2.402 GHz ... 2.48 GHz (ISM bandwidth)
Frequency band	2.4 GHz
Transmission power	max. 20 dBm (EIRP)
Number of wireless interfaces	1 IEEE 802.11 b/g/n
Wireless modules that can be connected	1

Wireless card

Number	1
Assembly instructions	Permanently installed

Antenna

Assembly instructions	Internal circularly polarized panel antenna
Number	1
Connection method	permanently installed

Power supply for module electronics

Connection method	M12 connector (A-coded, male)
Supply voltage	24 V DC
Supply voltage range	9 V DC ... 30 V DC
Supply current	76 mA (at 24 V DC)
Current consumption	76 mA (at 24 V DC)

Functions

Operating modes	Ethernet client adapter
Configuration	Web interface, MODE button, AT commands (TCP/IP), SSC
Automatic channel selection	Yes
Quality of service (QoS)	Yes
Security	802.11i
	WPA PSK (preshared key)
	WPA2 PSK
	AES
	WEP 64 bit/128 bit

Wireless module - FL WLAN EPA - 2692791

Technical data

Functions

	TKIP
	Supports 802.1X/RADIUS

Digital inputs

Number of inputs	1
------------------	---

General

Mounting type	Wall mounting
Net weight	240.8 g
Wireless licenses	Europe, USA, Canada, additional countries in the e-shop
Wireless licences	Belgium
	Bulgaria
	Denmark
	Germany
	Estonia
	Finland
	France
	Greece
	Great Britain
	Ireland
	Iceland
	Italy
	Canada
	Latvia
	Liechtenstein
	Lithuania
	Luxembourg
	Malta
	Netherlands
	Norway
	Austria
	Poland
	Portugal
	Romania
	Sweden
	Switzerland
	Slovakia
	Slovenia
	Spain
	Czech Republic
	Hungary
	USA

Wireless module - FL WLAN EPA - 2692791

Technical data

General

	Cyprus (rep.)
	Japan
Mounting type	Wall mounting

Standards and Regulations

Protection class	III, IEC 61140, EN 61140, VDE 0140-1
------------------	--------------------------------------

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>