

# RM Cores (6295140121)



Part Number: 6295140121

95 RM CORE SET

RM (Rectangular Modulus) cores allow better shielding than E type geometries while also providing easier winding accessibility and better power dissipation than a pot core configuration. Fair-Rite's standard RM cores all have a solid center post and standard height, low profile and alternate materials are available upon request.

RM cores can be supplied with the center post gapped to a mechanical dimension or an  $A_L$  value.

Weight indicated is per pair or set.

Weight: 3.2 (g)

Dim	mm	mm tol	nominal inch	inch misc.
A	14.3	± 0.30	0.563	
B	5.2	± 0.10	0.205	
C	6.6	± 0.20	0.26	
D	3.25	± 0.15	0.128	
E	10.4	± 0.20	0.409	
F	4.8	± 0.10	0.189	
G	6	min	0.236	min
J	12.05	± 0.25	0.474	

### Chart Legend

$\Sigma l/A$  : Core Constant,  $l_e$  : Effective Path Length,  $A_e$  : Effective Cross- Sectional Area,  $V_e$  : Effective Core Volume  
 $A_L$  : Inductance Factor

Explanation of Part Numbers: Digits 1 & 2 = product class and 3

& 4 = material grade.

Electrical Properties	
$A_L$ (nH)	1950 ±25%
$A_e$ (cm <sup>2</sup> )	0.233
$\Sigma l/A$ (cm <sup>-1</sup> )	10.3
$l_e$ (cm)	2.39
$V_e$ (cm <sup>3</sup> )	0.555
$A_{min}$ (cm <sup>2</sup> )	0.181

$A_L$  value is measured at 1 kHz, B < 10 gauss.