

**BT series**  
**TIMER BTDS-S**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com



BTDS installation timing relays for star/delta switchover in machine applications.

The timing relay is built into an Insta enclosure just 17.5 mm wide.

The relay contact is designed as a changeover contact with 250 V/5 A switching capacity.

**General ordering data**

Order No.	<a href="#">8647660000</a>
Type	TIMER BTDS-S
Version	BT series, Timing relay, No. of contacts: 2, NO contact, AgNi 90/10, Rated control voltage: 24...230 V AC, 24...48 V DC, Continuous current: 5 A, Screw connection
GTIN (EAN)	4032248308866
Qty.	1 pc(s).

**BT series  
TIMER BTDS-S**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data****Ratings**

Conductor connection system	Screw connection	Humidity	35...85 % rel. humidity, no condensation
UL 94 flammability rating	V-2		

**Dimensions and weights**

Width	17.5 mm	Height	80 mm
Depth	73 mm	Net weight	80 g

**Temperatures**

Operating temperature	-10 °C...+55 °C	Storage temperature	-25 °C...+65 °C
-----------------------	-----------------	---------------------	-----------------

**Input**

Rated control voltage	24...230 V AC, 24...48 V DC	Power rating	≤ 0.4 VA, 1.6 W
Time ranges	0.10 s - 120 h	Repeat accuracy	± 1 %

**Output**

Max. switching voltage, AC	250 V	Continuous current	5 A
----------------------------	-------	--------------------	-----

**Contact specifications**

No. of contacts	2	Contact design	NO contact
Contact material	AgNi 90/10	Mechanical service life	10 <sup>7</sup> switching cycles (no load, 1800/h)
Electrical service life, DC coil	10 <sup>5</sup> switching cycles (5A at 250 Vac, ohm load at 1800/h)	Contact resistance	100 MΩ min., at 500 V DC

**Insulation coordination**

Protection degree	IP 30 // terminals IP 20
-------------------	--------------------------

**Other technical data**

Version	Timing relay
---------	--------------

**Further details of approvals / standards**

Certificate No. (UR)	E223474OMR	Standards	UL508
----------------------	------------	-----------	-------

**Rated data UL**

Certificate No. (UR)	E223474OMR
----------------------	------------

**Classifications**

ETIM 2.0	EC001439	ETIM 3.0	EC001439
UNSPSC	30-21-19-17	eClass 4.1	27-14-23-10
eClass 5.1	27-14-23-10	eClass 6.0	27-14-23-10
eClass 7.0	27-14-23-10		

**Data sheet...**

**BT series  
TIMER BTDS-S**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Technical data**

**Approvals**

Approvals



**Downloads**

Declaration of Conformity [K258\\_08\\_03.pdf](#)