


JKL LAMP PART NO. (REFERENCE)	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms) @ 0°C	OPERATING LAMP VOLTAGE VL (Vrms) @ 25°C	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS) MINIMUM
CF26349-28B	x = .325 y = .295	1715	730	5 ± 1	30,000 ± 3000	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0.20 ANGLE +/- 0		JKL COMPONENTS CORPORATION					
					TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP							
A RATED LIFE HRS MINIMUM HEADING & 20,000 RELEASED & CANCEL P-0210-08 & BF26349-28B			DRAWN BY L. WENGSTROM		APPVD BY DATE L.R. 8/5/09		SIZE A	FSCM NO. 55335	DRAWING NO. CF26349-28B			
REV. NO. DESCRIPTION/ECO NUMBER APPVD DATE			- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE		RELEASED DATE 1/29/03	REVISION DATE 8/5/09	REV. NO. A	SHEET 1 OF 1		