



RESISTANCE @ +25°C = 10 Ω ± 20%
 MAXIMUM STEADY STATE CURRENT (I_{max}) = 10 AMPS
 RESISTANCE @ I_{max} = 0.10 Ω NOMINAL
 DIM "D" = 1.475" MAXIMUM
 DIM "T" = 0.350" MAXIMUM
 DIM "L" = 0.850" MINIMUM
 DIM "S" = 0.310" NOMINAL
 LEAD WIRE GAUGE = 18 AWG (0.040" DIAMETER)

SEE MANUFACTURING SPECIFICATION (LAYER 1)

"C"	DIM "D" WAS 1.250" MAXIMUM, DIM "T" WAS 0.300" MAXIMUM, DIM "L" WAS 1.50" MINIMUM, REMOVED SURGE RATING OF 180 JOULES & REMOVED VOLTAGE RATING OF 265 VAC (RMS)	07/14/09	DD
---	ISO RELEASE	06/03/03	DD
"B"	DIMENSION "T" WAS 0.250"	07/01/99	TW
"A"	ADDED MANUFACTURING SPECIFICATION (LAYER 1)	03/15/99	TW
REV	REVISION RECORD	DATE	APP

SCALE	NONE	U.S. SENSOR CORP. © COPYRIGHT 714-639-1000 www.ussensor.com INRUSH CURRENT LIMITER P/N ST10010B
DRAWN BY	DAN DANKERT	
DATE	07/29/98	
REV.	"C"	
LAYER	0 OF 2	