


**Part Number: 7916AP**

**DBS Cable, RG6, 18 AWG BC, Quad Shield, CMP**



## Product Description

18 AWG solid bare copper conductor, foam FEP insulation, Duobond® IV Quad shield (60% and 40% braid coverage), Flamarrest® jacket.

## Technical Specifications

### Product Overview

Environmental Space:	Indoor - Plenum
Suitable Applications:	Satellite Dish, KU Band

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Coax
18	Solid	BC - Bare Copper	0.04 in	1

Conductor Count:	1
Conductor Size:	18 AWG

#### Insulation

Material	Nominal Diameter
FFEP - Foam Fluorinated Ethylene Propylene	0.17 in

#### Outer Shield Material

Type	Layer	Material	Material Trade Name	Coverage [%]
Tape	1	Aluminum/Polyester/Aluminum	Bonded Duofoil®	100 %
Braid	2	AL - Aluminum		60 %
Tape	3	Aluminum/Polyester/Aluminum	Duofoil®	100 %
Braid	4	AL - Aluminum		40 %

#### Outer Jacket Material

Material	Material Trade Name	Nominal Diameter
LS PVC - Low Smoke Polyvinyl Chloride	Flamarrest®	0.248 in

### Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR	Outer Conductor DCR
6.4 Ohm/1000ft	4.8 Ohm/1000ft	4.8 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Shield
16.3 pF/ft

Shielding:	Multiple or Specialty
------------	-----------------------

#### Inductance

Nominal Inductance
0.097 µH/ft

#### Impedance

Nominal Characteristic Impedance
----------------------------------

75 Ohm

#### Return Loss (RL)

Frequency [MHz]	Min. Structural Return Loss (SRL)
5 - 1000 MHz	20 dB
1000 - 2250 MHz	15 dB
2250 - 3000 MHz	10 dB

#### High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
1 MHz	0.4 dB/100ft
10 MHz	0.7 dB/100ft
50 MHz	1.6 dB/100ft
100 MHz	2.1 dB/100ft
200 MHz	3 dB/100ft
400 MHz	4.3 dB/100ft
700 MHz	6.0 dB/100ft
900 MHz	7.0 dB/100ft
1000 MHz	7.5 dB/100ft

#### Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.24 ns/ft	83 %

#### High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)
1000 MHz	9 dB/100ft

#### Voltage

UL Voltage Rating
300 V RMS

### Temperature Range

Operating Temp Range:	-20°C To +75°C
-----------------------	----------------

### Mechanical Characteristics

Bulk Cable Weight:	29 lbs/1000ft
Max Recommended Pulling Tension:	137 lbs
Min Bend Radius/Minor Axis:	2.5 in

### Standards

NEC/(UL) Specification:	CATVP, CMP
CEC/C(UL) Specification:	CMP
RG Type:	6/U Type
Series Type:	Series 6
RG / Series Type:	Series 6

### Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

### Suitability

Suitability - Indoor:	Yes
-----------------------	-----

## Flammability, LS0H, Toxicity Testing

UL Flammability:	NFPA 262
CSA Flammability:	FT6
UL voltage rating:	300 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	Yes
---------------	-----

## Part Number

Non-Plenum Number:	7916A
--------------------	-------

## Variants

Item #	Color	Footnote
7916AP 8771000	Natural	C
7916AP 877U1000	Natural	

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.