



- NOTE:
- MATERIAL:
HOUSING: 30% GLASS FILLED PBT, THERMOPLASTIC, BLACK.
CONTACT: PHOS BRONZE
 - FINISH: CONTACT PLATING TIN (LEAD FREE); 60 UIN MIN. OVER 30 UIN NI
SOLDERABILITY :95% COVERAGE MIN.;
WORKING CONDITION:230°±5°C;
 - MECHANICAL SPECS:
DURABILITY: 50 CYCLES MIN.
INSERTION FORCE:300 GRAMS MAX.
WITHDRAWAL FORCE: 20 GRAMS MIN.
CONTACT RETENTION: 500 GRAMS MIN.
ACCEPTS: 0.20-0.30 [.008-.012] LEADS
 - ELECTRICAL SPECS:
VOLTAGE RATING: 250V AC,DC
CONTACT RESISTANCE: 20 MILLOHMS MAX.
CURRENT RATING: 1 AMPERE AC,DC
INSULATION RESISTANCE: 1000 MEGOHMS MIN.
DIELECTRIC WITHSTANDING VOLTAGE: AC 1000 V MIN.
 - OPERATING TEMPERATURE: -40°C TO +105°C
 - TE LOGO

△2	40	50.80	48.26	1-2199299-5
△2	28	35.56	33.02	1-2199299-2
FINISH	POS	A±0.20	B±0.15	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN WINNG WANG 18NOV2013	TE Connectivity
DIMENSIONS: mm		CHK SIMON LI 18NOV2013	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD COREL WANG 18NOV2013	NAME
0 PLG ±	1 PLG ±	PRODUCT SPEC	DIP SOCKET, .600 CENTER LINE LADDER STYLE
2 PLG ±	3 PLG ±	APPLICATION SPEC	
4 PLG ±	ANGLES ±	SIZE	A1
MATERIAL △1	FINISH △2-△7	WEIGHT	SCALE 5:1
CUSTOMER DRAWING		DATE 18NOV2013	SHEET 1 OF 1