

## Specification Sheet

Part Number: TSRP3I-8A



One Piece Power Rated Raceway, 1-3/4", 8.0 ft Long, PVC, Ivory, 160ft/Carton

**Article Number**

250-63801

**Type**

TSRP3-8A

**Color**

Ivory (IV)

### Features & Benefits

- Completely tamper resistant, the cover's self-locking, hidden positive latch permits quick re-entry as well as providing a secure installation of power cables.
- U.L. Listed for power up to 600 Volts, meeting UL5A and CSA 22.2 Number 62-93 Standards.
- Manufactured from UL 94V-0 rated PVC material.
- Fittings incorporate a minimum 1" bend radius per TIA/EIA 568-B and 569-A standards.
- Large base for greater adhesive surface.
- Rubber-based foam tape adhesive with high ultimate bond strength, which conforms to any surface.
- Flexible hinge allows the raceway to endure numerous openings without creating discoloration or stress cracking.
- Junction boxes can be used for electrical or data outlets.
- Designed to complement HellermannTyton's industry standard TSR low voltage raceway system.

**Quantity Per**

carton

**Product Description**

HellermannTyton's TSRP power surface raceway is a one piece, non-metallic, adhesive backed latching raceway designed to aesthetically organize and route either power or communications cables. Completely tamper resistant, the cover's self-locking, hidden positive latch permits quick reentry as well as providing a secure installation of power cables.

**Short Description**

One Piece Power Rated Raceway, 1-3/4", 8.0 ft Long, PVC, Ivory, 160ft/Carton

**Global Part Name**

TSRP3-8A-PVC-BGE

**Length L (Imperial)**

8.0

**Length L (Metric)**

2.44

**Width W (Imperial)**

1.75

**Width W (Metric)**

44.45

**Height H (Imperial)**

1.0

**Height H (Metric)**

25.40

**Material**

Polyvinylchloride (PVC)

**Material Shortcut**

PVC

**Halogen free**

No

**Reach Complaint(Article 33)**

No

**ROHS Complaint**

Yes

**Package Quantity(Imperial)**

160

**Package Quantity (Metric)**

48.80

**Customs Number**

3925900000