

used for: D-SUB HD

Directive 2002/95/EC RoHS compliant

NOTES:
 1. METALSHELLS: COPPER ALLOY; min. 320µin TIN
 2. INSULATORS: PBT GF UL 94 V-0, BLACK
 3. CONTACTS: COPPER ALLOY
 4. PLATING: GOLD FLASH over NICKEL
 5. SOLDER CUP ACCEPTS CABLE AWG 22

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH
 DO NOT ALTER CAD DRAWING BY HAND

tolerance	1999	date	02.11.	name	Barcinski
	drawn			appd.	Mickenbecker
	norm				
	d-old				

scale: 2:1
 material: SEE NOTES
 title: D-SUB HD MALE
 SOLDER CUP 62pos.
 for watertight hood
 dwg no: CAD/ REL.14 DIN-A 3
 product no: 18K 11F 4, A sh: 1/1
 4HDD62PAM99A10X

Grid labels: A, B, C, D, E, F (vertical); 1, 2, 3, 4, 5, 6, 7, 8 (horizontal)