

APPLICATOR PARTS LIST

TYPE
Lengthwise Ring

AMP INCORPORATED
HARRISBURG, PENNA.

NO.	DESCRIPTION	REQ.	PART NO.	NO.	DESCRIPTION	REQ.	PART NO.	CRIMPING DATA			TERMINALS
								WIRE SIZE	CRIMP HEIGHT		
1	WIRE CRIMPER 1-453921-3	1	2-464037-6	42				TO APPLY TERMINAL			61359
2	INS. CRIMPER	1	374888	43				18	.077		
3	ANVIL	1	4-570740-6	44							
4	ANVIL SPACER			45							
5	SHEAR BLADE	1	3-465233-4	46				16	.082		
6	REAR SHEAR PLATE	1	693088-1	47							
7	SHEAR BLADE SPACER	2	378193	48							
8	FRONT SHEAR PLATE	1	693089-1	49	Hold Down	1	811227-1	14	.088		
9	REAR ANVIL SPACER PLT.	1	693090-1	50				CRIMP SIZE	TYPE	FEED	
10	SPACER Tool	1	370296	51				WIRE .130	F	1.250	
11	TOOL SPACER	1	370701	52				INSUL. .180	F		
12	CRIMP SPACER	1	371220	53				SLEEVED			
13	FRONT STRIP GUIDE	1	693094-1	54				INSULATION RANGE	WIRE RANGE		
14	REAR STRIP GUIDE	1	693094-2	55				.090-.140	18-14		
15	RAM	1	471167	57				EXPLODED VIEW			
16	TOOL HOLDER	1	376046	58				A-6000 A-6000-3			
17	ADJ. CRIMP MOUNT Ass'y	1	465392-1	59				REMARKS:			
18	ADJ. BLOCK			60							
19	APPLICATOR MOUNT	1	693083-1	61							
20	BASE PLATE			62							
21	BASE BLOCK			63							
22	STRIP GUIDE PLATE			64							
23	ANVIL HOLDER	1	370526	65	Tension Adj. Plate	1	374999				
24	AUX. ANVIL HOLDER	1	377515		INCCELLANEOUS						
25	STRIPPER	1	810872-1	66	Lubricator	1	465166-2				
26	STRIPPER MOUNT 386231	1	372251	67	Oil, Synthetic	1	22014-1				
27	RETAINER PLATE	1	372251	68	24" REEL SUPPORT	1	565050-2				
28	STRIPPER MOUNT BRACKET			69	NIPPLE HEX. 1/2" x 1/8"	1	223048				
29	STRIPPER			70	VALVE, Flow Control	1	230531				
30	STOCK DRAG	1	375381	71							
31	STOCK DRAG HANDLE			72	AIR FEED ASSY (2")	1	690021				
32	STOCK DRAG STUD	2	354045	REV.	REVISION RECORD	DATE	BY	ECN			
33	STOCK DRAG SPRING	2	1-23847-1	A	RELEASED	8/19/68	DL				
34	STOCK DRAG ADJ. SCREW	2	372997	B	REV. PER E.C.N.	4/1/68	DL	L6204			
35	FEED FINGER HOLDER			C	REV PER ECN	12-8-70	ED	L7963			
36	FEED FINGER	1	379265	D	PER ECN	1-31-72	BM	L8694			
37	FEED FINGER TIP			E	REV PER ECN	2-28-73	JE	L9606			
38	FEED FINGER SPACER			F	REV PER ECN	6-5-74	JE	R555			
39	BASE CASTING	1	570238	G	26,29 69 70	9-13-75	DL	R1301			
40	GUARD 457664-2	1	471167	G1	INACTIVE PRO	1-24-77	DL	R1483			
41				G2	REACTIVATE	10/78	DL	R2709			

CRIMPING DATA				TERMINALS
TO APPLY TERMINAL				61359
WIRE SIZE	CRIMP HEIGHT			
18	.077			
16	.082			
14	.088			
CRIMP SIZE	TYPE	FEED		
WIRE .130	F	1.250		
INSUL. .180	F			
SLEEVED				
INSULATION RANGE	WIRE RANGE			
.090-.140	18-14			
EXPLODED VIEW				
A-6000 A-6000-3				
REMARKS:				

THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INCORPORATED AND THE CONTROLLING OFFICE SHOULD BE CONTACTED FOR THE LATEST REVISION.

■ DENOTES WEARING PARTS
RECOMMEND PURCHASE REPLACEMENT

THIS APPLICATOR IS TO BE USED ON
AMP-O-ELECTRIC 1-471273-2

ALIGN GAGE 679591-1	DIST. 4
SERIAL NO.	DATE SHIPPED
CUSTOMER NAME AND ADDRESS	DESIGNED
APPLICATOR NUMBER	REV. 3
565900-1	SHEET 1 OF 1

EC O150 4895 93 JEB/TB 10/93

H ECN A-393192 9/92 JH/B G3 ITEM (66) WAS-1 9-79 8/11/83 B3192

OK