

# Quick Charger Specification (FCT344)



<b>Compatible cells</b>	AA / AAA (1 ~ 4 cells), Individual charging		
<b>Input Voltage</b>	AC 100-240V, 50-60Hz		
<b>Charge Current</b>	AA: 1100mA (1~2cells),	550mA (3~4cells)	
	AAA: 560mA (1~2cells),	280mA (3~4cells)	
<b>Charge Time</b>		1~2 cells	3~4 cells
	AA (min.1900mAh)	Approx. 2 hrs	Approx. 4 hrs
	AAA (min.750mAh)	Approx. 1.5 hrs	Approx. 3 hrs
<b>Charge Control</b>	-ΔV, Timer		
<b>LED Indicator</b>	Charging: Turn On; Fully charging: Turn Off; Abnormal: Flashing		
<b>Safety function</b>	High temperature detection, Timer, Over-discharge cell detection, Reverse polarity charging prevention, Primary cell & End-of-Life cell detection		
<b>Temperature range</b>	0°C~35°C (Operating), -20°C~60°C (Storage)		
<b>Safety approval</b>	PSE (Japan), CE (Europe), ETL (USA), BSMI (Taiwan), SAA (Australia), KC (South Korea), BS (UK), EAC (Russia)		
<b>Dimensions / Weight</b>	108(L) x 68(W) x 28(H)mm / Approx. 100g		
<b>Others</b>	A plug [Japan, USA, Taiwan, Thailand, China], SE plug [South Korea], C plug [Europe, SP, Russia], BF plug [UK, HK, SP], O plug [Australia]		

**LED indicator**