


APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C
	OPERATING&STORAGE HUMIDTY RANGE	 85%MAX	APPLICABLE CABLE	CABLE DIAMETER : φ 8.3~9.3
	CURRENT		VOLTAGE	


SPECIFICATIONS


ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----

CONSTRUCTION


GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X

--	--	--	--	--

COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
 2	DIS-E-003060	TM. ONO	KN. ICHIKAWA	09. 12. 14

REMARK  THIS PRODUCT SHALL BE MATED WITH DH3*B-37S, IT APPLIES TO DH3*B-37S ABOUT A MECHANICAL, ENVIRONMENTAL CHARACTERISTICS. Unless otherwise specified, refer to JIS C 5402.	APPROVED	AO. SUZUKI	09. 04. 28
	CHECKED	KN. ICHIKAWA	09. 04. 28
	DESIGNED	MO. SHIMOYAMA	09. 04. 28
	DRAWN	MO. SHIMOYAMA	09. 04. 28

Note QT:Qualification Test AT:Assurance Test X:Applicable Test	DRAWING NO.	ELC4-126854-00
--	-------------	----------------

HRS	SPECIFICATION SHEET	PART NO.	DH-37-CT1B	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL244-0041-9-00	 1/1