



GAGE DIMENSIONS APPLY WHEN TOOL IS BOTTOMED BUT NOT UNDER PRESSURE.

FOR REPLACEMENT OF PARTS OTHER THAN LISTED, TOOL SHOULD BE RETURNED TO OUR FACTORY TO INSURE PROPER CERTI-CRIMP ADJUSTMENT.



ENLARGED VIEW OF CRIMP

"C" DIM. (16-14)	
GO	NO GO
.139	.145

"C" L.V.M. (22-16)	
GO	NO GO
.095	.101

REVISION RECORD	DR	CHK	DATE
J REVISED	B.S.	7/16/64	
H REVISED	BWS	8-22-63	
G REVISED	BWS	4-16-63	
F REVISED	C.M.	3-4-63	
E REDRAWN	C.M.	4-18-62	

NUMBER	DESCRIPTION
48208	

ITEM NO	NUMBER	NAME	REMARKS
8	48274	STOP	
7	2-21016-2	SCREW	
6	21045-6	RING - RETAINING	
5	300449	PIN - RETAINING	
4	39364	SPRING	
3	39366	COLLAR	
2	300432	PIN - RETAINING	
1	21045-3	RING - RETAINING	

DWG SIZE	NUMBER	NAME	REMARKS	ITEM NO
©1962 BY AMP INCORPORATED. ALL RIGHTS RESERVED. AMP PRODUCTS COVERED BY PATENTS AND/OR PATENTS PENDING.			<b>CUSTOMER COPY REFERENCE ONLY</b>	
DR	L. Osman 3-20-62		MATERIAL AND FINISH #	
CHK	E. J. ... 6-13-62		CLASS #	
DE			WIRE RANGE - INSULATION 18-16 #	
APP	E. J. ... 6-13-62		TYPE "C" PRE-INS. ECV-ECN	
TOLERANCE EXCEPT AS NOTED ± .015 ± .1" 0'			SCALE 1-1	LOC M
			NO B	REV J
			NAME <b>48208</b>	
<b>HAND TOOL ASSEMBLY</b>				

PRINT LIST 1289-3 DIMENSIONS IN INCHES DO NOT SCALE PRINT

8 7 6 5 4 3 2 1