

D see data sheet cable

Technical specification:

Rated voltage: IEC 61076-2-104	30 V
Current rating: IEC 61076-2-104	3 A at 40°C
Insulation resistance: IEC 60512	>=100 MΩ
Pollution degree: IEC 60664-1	3/2
Degree of protection: IEC 60529	IP 67, in mated condition
Temperature range: IEC 60664-1	-30°C ... +80°C
Mating cycles: IEC 60512-9a	>=100

Materials:


Contact:	CuZn
Contact plating:	Nickel, gold plated
Contact carrier:	TPU GF, UL 94
Sealing:	FPM
Coupling nut/ screw:	GD-Zn, nickel plated
Moulding body:	TPU, UL 94, grey

Installation specification:

Recommended torque:	0,6 Nm at width across flats 13
	0,4 Nm at width across flats 9

Conec installation tool:	Torque wrench:	36-000200
	Insert across flats 13:	36-000220
	Insert across flats 9:	36-000210

Contact assignment:



Part no:	Description:	Length L:	Cable:
43-05122	SAL - 12 - TS4 - TK4 - 8 - RK4 - 0,3 / A1	0,3m	PVC, grey, 4x0,25mm ² Cable: 781-A12400
43-05123	SAL - 12 - TS4 - TK4 - 8 - RK4 - 0,6 / A1	0,6m	
43-xxxxx	SAL - 12 - TS4 - TK4 - 8 - RK4 - ... / A1	x	

DO NOT ALTER CAD DRAWING BY HAND Directive 2002/95/EC RoHS compliant	Index: a 29.03.11 VF Ä3767 Coupling nut/ screw modified, spanner flats added, data sheet modified		title: T-Junction, male connector M12x1 - female connector M12x1 - female connector M8x1 axial	
	tolerance of cable: L ≤ 4m: L + 40mm L > 4m: L + 1%			date: 16.10.09 name: Fromm
	general tolerance: 0 ± 0,50mm 0,0 ± 0,25mm 0,00 ± 0,10mm	appd.: 16.10.09 name: Mankopf		dwg no: 43K1A1000
	THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH	part no: see table		