

LOC AI	DIST 00	REVISIONS				
P	LTR	DESCRIPTION	DATE	DWN	APVD	
A		INITIAL REVISION	12FEB2015	LS	CW	

HTV10L HAND TOOL, TAB 2.8 - SWS

FRONT VIEW

SIDE VIEW



Abmessungen / Dimensions:
 Länge/Length: 250 mm
 Breite/Width: 64.5 mm
 Tiefe/Depth: 26 mm

Eigenschaften / Features

Der Crimpkopf verfügt über drei Crimpnester in denen drei Leitungsquerschnitte 0.5, 0.75 und 1.0 mm² verarbeitet werden können. Die Kontakte werden mittels verschiebbarer Positionierer in der richtigen Position gehalten. Über eine längere Griffausführung wird die aufzubringende Kraft reduziert.

Crimping head with three crimping nests to apply 0.5, 0.75 and 1.0 mm² wire sizes. Contacts by means of slidable locator positioned. Crimping force reduced by means of long handles.

Ersatzteil / Spare part

HTV10L CRMP HEAD TAB 2.8 - SWS
 - TE P/N 8-1579016-4

Stückliste / Parts list

POS	TE- P/N	REV	QTY	DESCRIPTION
1	8-1579016-4	A	1	HTV10L CRMP HEAD TAB 2.8 - SWS
2	2-1579005-2	B	1	BASIC HAND TOOL GRIP, LONG, CS

CUSTOMER MANUAL: 411-18585 / 1-744017-4

Anwendungsbereich /
Application range

Leiterquerschnitt Cross section range (in sq.mm)	Leitercrimpöhe Conductor Crimp Height ±0,05 (in mm)	Leitercrimpbreite Conductor Crimp Width gemessen an den Tangenten der Radien in (mm)	Isolationscrimpöhe Insulation Crimp Height ±0,05 (in mm)	Isolationscrimpbreite Insulation Crimp Width gemessen an den Tangenten der Radien in (mm)	TE P/N- Kontakt TE P/N- Contact TIMER CONTACT (F2,8TAB)
0,5 / FLR	1,18	2,05 F	4,1	4,05 O	962915 / Strip foam 963748 / Loose- piece
0,75 / FLR	1,27				
1,0 / FLR	1,36				

THIS DRAWING IS UNPUBLISHED.
 BY TYCO ELECTRONICS CORPORATION.
 ALL INTERNATIONAL RIGHTS RESERVED.
 © COPYRIGHT

DIMENSIONS: mm	DWN L.Sandhu	12FEB2015	MATERIAL	FINISH
	CHK C. Witt	12FEB2015		
TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD C. Witt	12FEB2015		
	0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± -	PRODUCT SPEC	APPLICATION SPEC	SIZE A4
	WEIGHT 0.41kg	DRAWING NO 1579024-6	RESTRICTED TO -	
	CUSTOMER DRAWING	SCALE	SHEET 1 OF 1	REV A