



### CATHODE & GATE LEAD KITS



- WIRE COMPOSITION:**  
AWG 22, TINNED COPPER STRANDED WIRE WITH ETEF INSULATION RATED TO 125° C.
- LEAD COLOR:**  
RED (CATHODE) AND YELLOW (GATE). RED LEAD IS POSITIONED NEXT TO KEY ON BLACK POLARIZED HOUSING.
- RECEPTACLES:**  
FEMALE TERMINAL WITH LOCKING TAB FITS .11 x .03 IN. BLADES.

LEAD KIT TO ORDER	ORDER FOR MODULE	DESCRIPTION
LEAD KIT #NK	LD43-ND43-CD63-PD43 (FULL CONTROL)	LEAD SET 1 & LEAD SET 2 - ONE EACH/MODULE
LEAD KIT #NL	LD42-LS43-ND42-CD62 (HALF CONTROL)	LEAD SET 1 - ONE/MODULE
LEAD KIT #NM	LD47-ND47-CD67-PS43 (HALF CONTROL)	LEAD SET 2 - ONE/MODULE



- WIRE COMPOSITION:**  
AWG 22, TINNED COPPER STRANDED WIRE WITH ETEF INSULATION RATED TO 125° C.
- LEAD COLORS:**  
RED (CATHODE) AND YELLOW (GATE). BOTH WITH INSULATED TERMINALS.
- RECEPTACLES:**  
FEMALE TERMINAL WITH NYLON INSULATOR THAT FITS .11 x .03 IN. BLADE.

LEAD KIT TO ORDER	ORDER FOR MODULE	DESCRIPTION
LEAD KIT #MQ	CD43 (FULL CONTROL)	TWO RED & TWO YELLOW LEADS PER MODULE.
LEAD KIT #MR	CD42-CD47 (HALF CONTROL)	ONE RED AND ONE YELLOW LEAD PER MODULE