

SUMMARY



Image is for illustrative purpose only

Wires

Low	0
High	0
Coax	1
Triax	0
Quad	0
Fiber	0
Fluidic	0

Download

[Request a quote](#)

[Catalog](#)

Series	3T
Termination type	Female solder
IP rating	66
Cable Ø	0.00 - 0.00 mm
Matching parts	FFA.3T.275.CTAC75
Status	
Alternative part	

TECHNICAL DETAILS

Mechanics

Shell Style/Model	ERA*: Fixed socket, nut fixing
Keying	Circular (can rotate), plug has male contact(s)
Housing Material	Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces
Cable Fixing	∅ 0 - 0 mm
Variant	

Performance

Configuration	3T.275 : 1 Coax (75 Ohm)
Insulator	T: PTFE
Rated Current	6 Amps

Specifications


Contact Type:	Solder
Vtest:	(unknown)1200 V (AC), 1690 V (DC)
Impedance:	(unknown)75 Ohm

Others

Temp (min / max): -55° C / +200° C
Humidity (max): <=95% [at 60 deg C / 140 F]
Vibration: 15 g [10 Hz - 2000 Hz]
Shock Resistance: 100 g [6 ms]
Salt Spray Corrosion: >144 hr
Climatical Category: 50/175/21
Shielding (min): 75 dB (10 MHz)
Shielding (min): 40 dB (1 GHz)
IP Rating: 66

DRAWINGS

Draws



Dimensions

RECOMMENDED BY LEMO

Tools

None

Cables