

## Specification Sheet

Part Number: 126-00015



Domed Push Mount Tie, 6.3" Long, Fixing Hole Diameter .24" - .48", PA66HS, Black, 500/pkg

<b>Article Number</b>	126-00015
<b>Type</b>	T50SDOP
<b>Color</b>	Black (BK)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>•An all-in-one bundling and fixing solution reduces costs.</li><li>•Disc provides secure insertion and minimizes access of dust, dirt and water.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	The Domed Push Mount Tie provides a tight, rattle-free installation and acts as a seal to keep out dust and debris. One-piece mounting ties offer a complete solution by both bundling cable and at the same time providing a mounting solution.
<b>Short Description</b>	Domed Push Mount Tie, 6.3" Long, Fixing Hole Diameter .24" - .48", PA66HS, Black, 500/pkg

Global Part Name

T50SDOP-PA66HS-BK

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

225.0

Length L (Imperial)

6.3

Length L (Metric)

160.0

Fixation Method

Arrowhead for oval holes

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.2

Width W (Metric)

5.0

Bundle Diameter Min (Imperial)

0.2

Bundle Diameter Min (Metric)

5.0

Bundle Diameter Max (Imperial)

1.2

Bundle Diameter Max (Metric)

30.0

Thickness T (Imperial)

0.05

<b>Thickness T (Metric)</b>	1.3
<b>Height H (Imperial)</b>	0.36
<b>Panel Thickness Min(Imperial)</b>	0.04
<b>Panel Thickness Max(Imperial)</b>	0.08
<b>Panel Thickness Min (Metric)</b>	1.0
<b>Panel Thickness Max (Metric)</b>	1.9
<b>Mounting Hole Diameter D (Imperial)</b>	0.24 - 0.27
<b>Mounting Hole Diameter D (Metric)</b>	6.2 - 12.2 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.244
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.27
<b>Mounting Hole Diameter D Max (Metric)</b>	12.2
<b>Disc Diameter(Metric)</b>	22.0
<b>Disc Diameter (Imperial)</b>	0.87
<b>Stud Length Min (Metric)</b>	9.2
<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Shortcut</b>	PA66HS

<b>Flammability</b>	UL 94 V2
<b>Operating Temperature (Metric)</b>	-40°F to +221°F (-40°C to +105°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	500
<b>Package Quantity (Metric)</b>	500
<b>Customs Number</b>	3926909987
<b>Content Unit(BMEcat)</b>	pcs.
<b>Weight (Metric)</b>	1.7